Technical Data Sheet

2/13/2015

Model: VSA9521ZXG

Version: N/A

Product Description

Type:	Scroll
Application:	CBP - Commercial Back Pressure
Refrigerant:	R-404A
Voltage/Frequency:	460V 3~ 60Hz 380-420V 3~ 50Hz

Product Specifications

General

Evaporating Temp. Range:	-17.8°C to 10°C (0°F to 50°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	75
Weight Unit of Measure:	LB
Displacement (cc):	50.15
Oil Type:	Polyolester
Viscosity (cSt):	24
Oil Charge (cc):	710

Electrical

Voltage Range (50 Hz):	342-462
Voltage Range (60 Hz):	414-506
Locked Rotor Amps (LRA):	40.4
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	5.4
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	4.09
Motor Resistance (Ohm) - Start:	N/A
Motor Type:	3PH
Overload Type:	N/A
Relay Type:	N/A

Agency Approval

CE Listed, cURus Recognized